



NOTES:

A. Material:

1. Insulator: High temperature thermoplastic UL94V-0, (BLACK LCP)
2. Beryllium copper: Plating, gold(3-8U") over nickel(50-80U")
3. Pho. Bronze: Plating, Tin(100-120U") over nickel(50-80U")

B. Electrical specifications:

- Voltage rating: 12 VAC
 Current rating: 2.0A
 Dielectric strength: 250V AC for 1 minute
 min Insulation resistance: 500 M ohm
 min Contact resistance: 50 mill.ohm max
 Operation temperature: -40°C to +105°C
 Product withstanding rff low soldering 260°C for 10s

C. Mechanical specifications:

- 3.1 Durability: 5000 cycles
- 3.2 Normal force at working position: 80g min

A	B	C
1.5~~1.9	1.70±0.15	6.00
1.9~~2.3	1.70±0.15	7.00

??REV.	????REVISIONNO	DATE	未注公差 TOLERANCE	深圳市正久电子科技有限公司
			X. ±0.15 X.' ±1'	
			X.X ±0.10 X.X' ±0.5'	
绘制DRAWN	张文明		X.XX ±0.05 X.XX' ±0.05'	零件PART NO:
设计DES' D	赵聪		X.XXX ±0.005 X.XXX' ±0.005'	图号DRAWING NO:
审核CHK' D	黄伟霖		视图方法 PROJECTION	立式ZJ-3P-2.5PH-6.0(7.0)H带中柱 内焊
批准APPV' D	王燕信		比例SCALE: 3:1	单位UNIT: mm 页码SHEET: 共1页 第1页

