



**Bill Of Materials:**

No.	TITLE	MATERIAL	FINISH(OR COLOR)	NO.
1	HOUSING	LCP+30%GF,UL94 V-0	BLACK	1
2	TERMINAL	C5210R-H,T=0.15mm	3u" GLOD PLATED	4
3	GROUND SLICE	BRASS(C2680R-H),T=0.20mm	TIN PLATED	2
4	GO TO SLICE	BRASS(C2680R-H),T=0.20mm	TIN PLATED	2

**SPECIFICATION:**

- CURRENT RATING:0.5A 50V AC/DC.
- CONTACT RESISTANCE:60mΩ MAX AT DC 20mA.
- INSULATION RESISTANCE:100MΩ MIN AT 500V DC.
- OPERATING TEMPERATURE RANGE:-25°C TO +85°C.
- MARKED "▼" ARE IMPORTANT DIMENSIONS.

REV	ECN DESCRIPTION	DATE	CHANGE
A/1	整理图面及增加料号说明	2009-06-05	张文明

深圳市正久电子科技有限公司  
SHENZHEN ZHENGJIU ELECTRONICS CO.,LTD

UNIT: mm  
SCALE: 1:1  
PAGE: 1/1

DESIGN: Sword 6/05/2009  
DRAW:  
APPRO: 工程部专用章

TITLE: 电池弹片  
P/N: 立式ZJ-4P-2.5PH-6.5H带柱

