



RECOMMENDED PCB LAYOUT
T=1.2MM, TOLERANCES±0.05MM

REV.	DESCRIPTION	DRAW.	DATE.

NOTE:

- MATERIAL:
 - HOUSING: PA9T, UL 94V-0
 - TERMINAL: C2680
- FINISH:
 - TERMINAL: NICKEL 50 μ M UNDER PLATED
OVERALL, Au PLATED ON THE CONTACT AREA.
OR Tin ON THE SOLDERING AREA.
- PRODUCT SPECIFICATION
 - CURRENT RATING : 5A
 - VOLTAGE RATING : 30V AC
 - DIELECTRIC WITHSTANDING VOLTAGE: 500VAC
 - INSULATIC RESISTANCE: 100M Ω min.
 - CONTACT RESISTANCE: 30m Ω Max.
 - Operating Temperature: -40° ~105°

No. of Pins	Dimension	
	DIM.B	DIM.A
03	5.00	10.00
04	7.50	12.50
05	10.00	15.00
06	12.50	17.50
07	15.00	20.00
08	17.50	22.50
09	20.00	25.00
10	22.50	27.50
11	25.00	30.00



深圳市正久电子科技有限公司
 SHENZHEN ZHINEJIU ELECTRONICS CO.,LTD

UNLESS OTHERWISE SPECIFIED, TOLERANCE: X. ±0.8 X.x ±0.35 X.xx ±0.25 ANGULAR ±2°	DESIGN	Y.Q.H	DATE	2014.08.28	TITLE:	B01M-R2	
	APPROVED		DATE				
PART NO			REV: 01	SCALE: 1:1	UNIT: MM		
DRAWING NO			SIZE: A4	SHEET: 1/1			